



Hilberling

Hilberling GmbH · Entwicklungslabor · Hochfrequenztechnik

Heinrich-Hertz-Straße 2 · D - 24790 Schacht-Audorf

eMail: info@hilberling.de · www.hilberling.de

HPS48-20/6

Power Supply
for HF Power Amplifiers





Project: Power Supply

Technical Data

AC Connectors

- Supply Voltages AC IN 6 x 100 V ... 240 V / 50 ... 60 Hz / 15 A
- Connector type: IEC C20 / separate Fuse Protection

DC Connectors

- Output Voltages DC OUT 3 x +54 V / 45 A (2 x 22.5 A)
- Connector type: CliffCon FCR2068

Status LEDs

- AC Stand-by 6 x LED green
- DC-OUT 6 x LED green

Temperature Range

- Operation 0 ... +40°C
- Storage 0 ... +70°C

Cooling

- Air Cooling active by Fans
- Air Entrance Front Panel
- Air Outlet Rear Panel

Housing

- Material Sheet Steel / Front Panel Aluminum
- Dimensions 19" / 5HU / Depth 460 mm
- Weight 20.8 kg



Hilberling

HF-Entwicklungslabor eMail: info@hilberling.de

Heinrich-Hertz-Str. 2 24790 Schacht-Audorf

Data Sheet / Specification

HPS48-20/6

Project: Power Supply

Outline Drawings

